

## FLANGE PLATE EN 1092-01/02- SS 304



**Swivel flange, flange type EN 1092-01/02** (previous version DIN 2576), made of AISI 304 stainless steel. The flange is available in a wide range of sizes: from DN 10 to DN 150—standard PN 10/40 or PN 10/16, depending on the size.

**IMPORTANT:** This collar is intended for connection to the thin version of the TW FRS hose ends.

|          |                          |
|----------|--------------------------|
| Material | Stainless steel AISI 304 |
| Version  | Thin                     |
| Norm     | EN 1092-01/02            |

| Variant   | Size   | Number of holes/ hole diameter | Inside flange | Outer flange | Work pressure - BAR | Weight (kg) |
|-----------|--------|--------------------------------|---------------|--------------|---------------------|-------------|
| FP02010SS | DN 10  | 4/60                           | 21            | 90           | PN 10/40            | 0,6         |
| FP02015SS | DN 15  | 4/65                           | 25            | 95           | PN 10/40            | 0,5         |
| FP02020SS | DN 20  | 4/75                           | 31            | 105          | PN 10/40            | 1           |
| FP02025SS | DN 25  | 4/85                           | 38            | 115          | PN 10/40            | 2           |
| FP02040SS | DN 40  | 4/110                          | 53            | 150          | PN 10/40            | 2           |
| FP02050SS | DN 50  | 4/125                          | 65            | 165          | PN 10/40            | 2,7         |
| FP02065SS | DN 65  | 4/145                          | 81            | 185          | PN 10/16            | 3,4         |
| FP02080SS | DN 80  | 8/160                          | 94            | 200          | PN 10/16            | 4,2         |
| FP02100SS | DN 100 | 8/180                          | 120           | 220          | PN 10/16            | 5,9         |
| FP02125SS | DN 125 | 8/210                          | 145           | 250          | PN 10/16            | 8           |
| FP02150SS | DN 150 | 8/240                          | 174           | 285          | PN 10/16            | 10          |