

## TW SAFETY CLAMP EN 14420-3- ALUMINIUM



**TW safety clamp made of aluminum**, compatible with TW hosetails (smooth tail and serrated tail with collar).

This safety clamp is mounted with 4, 6, or 8 bolts, depending on the clamp size.

Material	Aluminum
Norm	EN 14420-3
Bolt material	Galvanized steel

Variant	Clamp range (mm)	Bolt	Hose size (mm)
TWSC022AL	22-24	M6 x 20	13 x 5
TWSC030AL	30-33	M6 x 20	19 x 6
TWSC034AL	34-36	M6 x 20	25 x 5
TWSC036AL	36-39	M6 x 20	25 x 6
TWSC041AL	41-43	M6 x 20	32 x 5
TWSC043AL	43-46	M6 x 20	32 x 6
TWSC047AL	47-50	M6 x 20	32 x 8
TWSC0472AL	47-49	M6 x 20	38 x 5
TWSC050AL	50-52	M6 x 20	38 x 6,5
TWSC053AL	53-56	M6 x 20	38 x 8
TWSC059AL	59-61	M8 x 25	50 x 5
TWSC061AL	61-63	M8 x 25	50 x 6
TWSC064AL	64-67	M8 x 25	50 x 8
TWSC069AL	69-71	M8 x 25	50 x 10
TWSC074AL	74-76	M8 x 25	63 x 6
TWSC078AL	78-82	M8 x 25	63 x 8
TWSC084AL	84-87	M8 x 25	65 x 10
TWSC086AL	86-88	M8 x 25	75 x 6
TWSC089AL	89-93	M8 x 25	75 x 8
TWSC094AL	94-97	M8 x 25	75 x 10
TWSC098AL	98-101	M8 x 25	75 x 12
TWSC0942AL	94-97	M8 x 25	80 x 8
TWSC112AL	112-114	M10 x 40	100 x 6,5
TWSC114AL	114-119	M10 x 40	100 x 8
TWSC118AL	118-122	M10 x 40	100 x 10
TWSC122AL	122-126	M10 x 40	100 x 12
TWSC143AL	143-148	M10 x 40	125 x 10
TWSC168AL	168-174	M12 x 50	150 x 10
TWSC174AL	174-180	M12 x 50	150 x 13
TWSC222AL	222-229	M12 x 60	200 x 12
TWSC274AL	274-278	M12 x 60	250 x 13