

## RADIATOR 3D EPDM 125



**The rubber radiator hose is suitable for coolant systems,** designed to transfer cooling water, glycol, and antifreeze fluids.

Thanks to its construction, the hose offers good resistance to UV, ozone, chemicals, and abrasion.

|                   |                               |
|-------------------|-------------------------------|
| Inner wall        | EPDM                          |
| Outer wall        | EPDM                          |
| Reinforcement     | Strong textile reinforcements |
| Work pressure     | 3 BAR                         |
| Burst pressure    | 9 BAR                         |
| Temperature range | -30°C to +125°C               |

| Variant | Inner Diameter<br>(mm) | Outer Diameter<br>(mm) | Weight<br>(g/m) | Coil<br>(m) |
|---------|------------------------|------------------------|-----------------|-------------|
| 1000001 | 16                     | 23                     | 460             | 40          |
| 1000002 | 22                     | 28                     | 600             | 40          |
| 1000003 | 25                     | 33                     | 650             | 40          |
| 1000004 | 28                     | 35                     | 720             | 40          |
| 1000005 | 30                     | 38                     | 760             | 40          |
| 1000006 | 32                     | 40                     | 810             | 40          |
| 1000007 | 35                     | 43                     | 870             | 40          |
| 1000008 | 38                     | 46                     | 940             | 40          |
| 1000009 | 40                     | 48                     | 970             | 40          |
| 1000010 | 42                     | 51                     | 1020            | 40          |
| 1000011 | 45                     | 53                     | 1070            | 40          |
| 1000012 | 48                     | 58                     | 1150            | 40          |
| 1000013 | 50                     | 60                     | 1190            | 40          |
| 1000014 | 55                     | 65                     | 1270            | 40          |
| 1000015 | 60                     | 70                     | 1350            | 40          |
| 1000016 | 65                     | 73                     | 1480            | 40          |
| 1000017 | 70                     | 80                     | 1520            | 40          |
| 1000018 | 75                     | 85                     | 1620            | 40          |
| 1000019 | 80                     | 90                     | 1900            | 40          |
| 1000020 | 90                     | 100                    | 2065            | 40          |
| 1000021 | 102                    | 112                    | 2260            | 40          |
| 1000022 | 110                    | 124                    | 2400            | 40          |