

## RADIFLEX 120 EPDM SD



**A highly flexible rubber hose for hot water, glycol, coolant, and light water-based chemicals.** Its key feature is the ability to operate in very tight spaces where flexibility is crucial. Unlike standard coolant hoses, this hose is reinforced with a steel spiral, allowing for a broader range of applications in various installations. It is often used on motorboats and motor yachts to transfer cooling water. The outer wall is resistant to abrasion and external conditions, including UV rays, ozone, and aging.

Inner wall	EPDM
Outer wall	EPDM
Reinforcement	Strong textile reinforcement, steel spiral
Work pressure	5 BAR
Burst pressure	15 BAR
Temperature range	-40°C to +120°C

Variant	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Coil (m)
83001624	16	24	30	20
83001826	18	26	35	20
83001929	19	29	40	20
83002028	20	28	40	20
83002230	22	30	45	20
83002533	25	33	50	20
83002836	28	36	55	20
83003038	30	38	60	20
83003242	32	42	65	20
83003545	35	45	70	20
83003848	38	48	80	20
83004050	40	50	85	20
83004252	42	52	85	20
83004555	45	55	90	20
83004858	48	58	120	20
83005161	51	61	120	20
83005565	55	65	140	20