

MULTI-ARA SBR 10 SD



Multifunctional rubber SD hose reinforced with one or two textile plies and a steel spiral.

It is highly suitable for use as a slurry tanker hose (especially in the largest vehicles), as part of an elastic pipeline, or as a hose for slurry water. Thanks to the SBR rubber, both the outer and inner layers are abrasion-resistant.

Inner wall	SBR
Outer wall	Black SBR
Reinforcement	One or two textile reinforcements (depending on diameter), steel spiral
Work pressure	10 BAR
Burst pressure	30 BAR
Temperature range	-25°C to +70°C

Variant	Inner Diameter (mm)	Outer Diameter (mm)	Vacuum (BAR)	Bending Radius (mm)	Weight (kg/m)	Coil (m)
1000730	50	60	1,00	152	1,3	40
1000731	60	71	1,00	180	1,5	40
10007001	70	82	0,9	280	2,12	40
1000708	76	88	0,9	324	2,29	40
1000732	80	93	0,9	200	2,34	20
1000734	100	113	0,9	300	2,99	20
1000711	102	116	0,9	408	3,2	40
1000720	110	126	0,8	440	3,4	40
1000713	127	141	0,8	635	5,02	20
1000714	152	169	0,8	760	6,25	20
1000715	203	224	0,7	1015	10,58	20
10007241	254	272	0,6	1270	12,7	5