

LACTERA ALIKLER SD FDA NBR



Flexible and easy-to-handle dairy rubber hose with spiral reinforcement and smooth construction. Thanks to the NBR inner wall, the hose is suitable for fatty products, as well as milk, wine, beer, cider, fruit juices, and alcohol up to 95%.

The hose is suitable for sterilization using the CIP (Clean-In-Place) method and the steam method up to +130 °C (for short periods).

Inner wall	NBR – white			
Outer wall	NBR – PVC – blue			
Reinforcement	Textile reinforcement, steel spiral			
Work pressure	10 bar			
Burst pressure	30 bar			
Vacuum	90%			
Temperature range	-30 °C to +80 °C			
Norms	BfR XXI cat 2, EU 2023/2006, EU regulation nr. 1935/2004, FDA 21 CFR 177.2600, French legislation			





Variant	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Coil (m)	Weight (g/m)
1510001	25	36	50	40	700
1510011	32	43	64	40	820
1510012	38	49	76	40	1140
1510002	40	51	80	40	1270
1510003	51	63	102	40	1790
1510009	53	65	106	40	1850
1510004	63	75	126	40	2170
1510010	70	83	140	40	2620
1510005	76	89	152	40	3030
1510007	100	114	350	40	3670