

ADARA LIGHTFLEX SD NR-SBR



Lightweight and highly flexible, this rubber hose is designed for vacuum loader trucks and slurry tankers (e.g., DISAB, WUKO). It is highly recommended for use with articulated arms or truck-mounted hose reels, thanks to its exceptional flexibility and durable construction.

Suitable for light solvents, slurry water, and various other industrial uses. The hose maintains excellent flexibility even at temperatures as low as -40°C.

Inner wall	NR-SBR
Outer wall	Square corrugated SBR
Reinforcement	One or two textile reinforcements, steel spiral
Work pressure	6 bar
Burst pressure	18 bar
Vacuum	0,92 bar
Temperature range	-40°C to +70°C

Variant	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Weight (kg/m)	Coil (m)
1000863	102	123	280	3,9	40
1000793	127	143	318	6,26	3
1000796	127	143	318	6,26	4
1000791	127	143	318	6,26	20
1000794	152	168	381	7,5	2,5
1000848	152	168	381	7,5	3
1000852	152	168	381	7,5	6
1000792	152	168	381	7,5	20
1000799	160	176	405	7,45	20
1000853	203	224	508	13,11	6
1000795	203	224	508	13,11	20