

MULTI-CHEM EPDM OHM SD



Chemical-resistant hose with spiral reinforcement, suction-discharge type, designed for transferring chemically aggressive fluids such as acids, bases, solvents, and paints. The hose's outer wall is resistant to abrasion, wear, and environmental conditions, including UV radiation and ozone.

The hose is fully conductive, with electrical resistance values of $R < 10^6 \Omega$ and $R < 10^9 \Omega$ through the wall.

The hose complies with the EN 12115:2011 standard.

Inner wall	EPDM
Outer wall	Black EPDM
Reinforcement	Two textile reinforcements, steel spiral
Work pressure	16 BAR
Burst pressure	64 BAR
Temperature range	-35°C to +100°C
Norms	EN 12115:2011

Variant	Inner Diameter (mm)	Outer Diameter (mm)	Vacuum – BAR	Bending Radius (mm)	Weight (kg/m)	Coil (m)
40700019	19	31	0,9	125	0,69	40
40700025	25	37	0,9	150	0,84	40
40700032	32	44	0,9	175	1,03	40
40700038	38	51	0,9	225	1,18	40
40700050	50	66	0,9	275	1,73	40
40700063	63	79	0,9	300	2,33	40
40700076	76	92	0,8	350	2,76	40
40700102	102	120	0,8	450	3,78	40