

MULTI-WATER EPDM OHM 10 SD



Multi-purpose industrial hose reinforced with steel spiral, suction-discharge type. Suitable for the transfer of various fluids such as hot water, light chemicals, glycol, or industrial dirty water. It can also serve as an air compressor hose. It finds application in environments such as septic tank vehicles, HVAC chillers, or pipeline components. The hose's outer wall is resistant to abrasion and challenging environmental conditions, including UV radiation and ozone. The hose is conductive, i.e. $R < 10^6 \Omega$ through the wall.

Inner wall	EPDM
Outer wall	Black EPDM
Reinforcement	Two textile reinforcements, steel spiral
Work pressure	10 BAR
Burst pressure	30 BAR
Temperature range	-35°C to +120°C

Variant	Inner Diameter (mm)	Outer Diameter (mm)	Vacuum (BAR)	Bending Radius (mm)	Weight (kg/mb)	Coil (mb)
10001929	19	29	1	76	0,59	61
10002535	25	35	1	100	0,72	61
10002535	32	42	1	128	0,89	61
10003849	38	48	1	152	1,16	61
10005161	51	61	1	204	1,45	61
10006375	63	75	0,9	252	2,00	40/61
10007688	76	88	0,9	304	2,30	40/61
10090104	90	104	0,9	356	3,01	40/61
10102116	102	116	0,9	408	3,80	40/61
10127142	127	142	0,9	608	5,01	61
10152166	152	166	0,9	760	6,66	40/61
10203221	203	221	0,9	812	9,88	61