

HEAVY MULTI 20 D



A highly durable, multi-purpose discharge hose suitable for conveying compressed air (including oil-laden air), industrial water, and slurry.

It is used, for example, as a high-pressure hose with claw-type connectors such as ATLAS COPCO, to power pneumatic hammers, and as a pipeline component.

The outer wall is resistant to UV radiation, ozone, harsh environmental conditions, abrasion, and light chemicals. Thanks to the synthetic rubber blend inside, the hose resists wear and oil-contaminated environments.

| | |
|-------------------|----------------------------|
| Inner wall | SBR |
| Outer wall | EPDM |
| Reinforcement | Two textile reinforcements |
| Working pressure | 20 BAR |
| Burst pressure | 60 BAR |
| Temperature range | Temperature range |

| Variant | Inner Diameter (mm) | Outer Diameter (mm) | Coil (m) |
|----------|---------------------|---------------------|----------|
| 25400019 | 19 | 30 | 61 |
| 25400025 | 25 | 37 | 61 |
| 25400032 | 32 | 44 | 61 |
| 25400038 | 38 | 52 | 61 |
| 25400050 | 51 | 66 | 61 |
| 25400060 | 63 | 79 | 40 |
| 25400075 | 76 | 92 | 40 |
| 25400102 | 102 | 118 | 40 |